
Upper Ocean Microstructure and Air-Sea Fluxes

Brian Ward

University College Galway, Ireland

February 23, 2011

Shiptime for SPURS



- An pre-application for ship time for the R/V Celtic Explorer has been submitted
- Next call for ship time is October 2011
- SMOSPROC: ESA-funded post-doc starting March 01 with salinity/microstructure as the focus
- ASIP-funded project with Norwegian MET.NO waves/turbulence
- PI Proposal pending with Science Foundation Ireland
- PhD Fellowship proposal pending with Canadian Research Council


Air—Sea Interaction Profiler (ASIP)



- By profiling vertically towards the air-sea interface, ASIP provides detailed measurements of the undisturbed water
- Features
 - Positively buoyant instrument submerged with a thruster
 - Measurements made during ascent only
 - Maximum depth 100m
 - Onboard power 1000 Whr from Li–ion batteries
 - GPS receiver to determine position
 - Iridium modem for transmitting position and mission parameters




ASIP Sensors




- Shear (turbulence)
- 1-D doppler
- Microstructure temperature
- Microstructure conductivity
- Slow temperature & conductivity
- Oxygen
- PAR.
- Pressure
- Adding a hydrophone for a criuse in Norway in April

ASIP Profile




• ASIP shear spectra closely follow the Nasmyth Spectrum expected for isotropic turbulence

Indian Ocean: Turbulent dissipation




- The black line represents the mixing layer depth
 (D) which represents the depth of active mixing
- Dramatic change in D with increased buoyancy flux
- Dissipation under these conditions scales with law of the wall (wind 2-6 ms^{-1})


Shear Distribution




Temperature Labrador Sea : Low winds $(<5 \text{ ms}^{-1})$




Salinity Labrador Sea: Low winds $(<5 \text{ ms}^{-1})$



Shipboard Flux Mast





- Air-sea heat and H2O fluxes i.e. eddy covariance
- Tripod base allows ease of installation

Sailbuoy: Christen Michelsen Research (cmr.no)





- Payload: 10 kg / 60 dm³
- Average speed: 1-2 knots
- Navigable wind speed range: 2-20 ms^{-1}
- http://www.youtube.com/watch?v=K_3vZDbQQI